




| | |
|--------------------------------|------------------|
| Produkt Data Sheet | Art. No.: FE-B01 |
| Foldable Bucket: FE-B01 | Status: 2-1-2021 |

| | |
|--|---|
| <p>Article Picture</p> <div style="text-align: center;">  <p>FE-B01</p> </div> | <p>Article Description</p> <p>Foldable tool bucket for lifting tools and materials securely up to 15 kg to higher work places.</p> <p>Made of strong double layer weatherproof polyester fabric and a 4 mm rubber bottom insert.</p> <p>The opening is stabilized by a coated steel ring.</p> <p>For transport it folds to minimum volume.</p> |
| <p>Technical Data:</p> <ul style="list-style-type: none"> • WLL (working load limit) [kg]: 15 • Safety factor: 7 • Material: <ul style="list-style-type: none"> ○ Corpus: double layer PVC coated Polyester fabric Oxford 600D ○ Webbing: Polyester fabric, 38 mm ○ Bottom: HDPE ○ Insert: Virgin rubber, 4mm strong • Content [l]: 21 • Diameter top [mm]: 260 • Diameter bottom [mm]: 260 • Height[mm]: 400 • Net weight [g]: approx. 1200 | <p>Range of Application:</p> <ul style="list-style-type: none"> • Power line construction • Railway line construction • Industrial construction • Free climbing work • ... and many others more. |
| <p>Information for use:</p> <p>Maximum service life: 5 years from date of manufacture.</p> <p>Visual and functional check before use. If you recognize damage of webbing, corpus or bottom, it has to be withdrawn from operation.</p> <p>Inspection in accordance with legal national guidelines but at least once a year.</p> | |
| <p>Certificates/ Assessments:</p> <p>Lifting load test executed by the „Sächsische Textilforschungsinstitut e.V.“(STFI)</p> | |

| | | |
|-------------|---|------------------------|
| HP-TEC GmbH | Kirchenlamitzerstraße 100, D-95213 Münchberg | www.hp-tec-produkte.de |
|-------------|---|------------------------|