




Produkt Data Sheet	Art. No.: FE-B02
Foldable Bucket: FE-B02	Status: 22-2-2025

Article Picture  <p>FE- B02</p>	Article Description <p>Foldable tool bucket for lifting tools and materials securely up to 15 kg to higher work places.</p> <p>Made of strong double layer weatherproof polyester fabric and a 4 mm rubber bottom insert.</p> <p>The opening is stabilized by a coated steel ring.</p> <p>For transport it folds to minimum volume.</p>
Technical Data: <ul style="list-style-type: none"> • WLL (working load limit) [kg]: 15 • Safety factor: 7 • Material: <ul style="list-style-type: none"> ○ Corpus: double layer PVC coated Polyester fabric Oxford 800D ○ Webbing: Polypropylene fabric, 38 mm ○ Bottom: HDPE ○ Insert: Virgin rubber, 4mm strong • Content [l]: 22 • Diameter top [mm]: 300 • Diameter bottom [mm]: 260 • Height[mm]: 360 • Net weight [g]: approx. 1200 	Range of Application: <ul style="list-style-type: none"> • Power line construction • Railway line construction • Industrial construction • Free climbing work • ... and many others more.
Information for use: <p>Maximum service life: 5 years from first use.</p> <p>Visual and functional check before use. If you recognize damage of webbing, corpus or bottom, it has to be withdrawn from operation.</p> <p>Inspection in accordance with legal national guidelines but at least once a year.</p> <p>Writing or marking with solvent-based pencil on lifting webbing is not allowed.</p>	
Certificates/ Assessments: <p>Lifting load test executed by the „Sächsische Textilforschungsinstitut e.V.“(STFI)</p>	

HP-TEC GmbH	Kirchenlamitzerstraße 100, D-95213 Münchberg	www.hp-tec-produkte.de
-------------	-------------------------------------------------	------------------------