




<b>Produkt Data Sheet</b>	Art. No.: FE-B03
<b>Foldable Bucket: FE-B03</b>	Status: 22-2-2025

<b>Article Picture</b>  FE-B03	<b>Article Description</b> <p>Foldable tool bucket for lifting tools and materials securely up to 25 kg to higher work places.</p> <p>Made of strong double layer weatherproof polyester fabric and a 4 mm rubber bottom insert.</p> <p>The opening is stabilized by a coated steel ring.</p> <p>For transport it folds to minimum volume.</p>
<b>Technical Data:</b> <ul style="list-style-type: none"><li>• WLL (working load limit) [kg]: 15</li><li>• Safety factor: 7</li><li>• Material:<ul style="list-style-type: none"><li>○ Corpus: double layer PVC coated Polyester fabric Oxford 800D</li><li>○ Webbing: Polypropylene fabric, 38 mm</li><li>○ Bottom: HDPE</li><li>○ Insert: Virgin rubber, 4mm strong</li></ul></li><li>• Content [l]: 22</li><li>• Diameter top [mm]: 380</li><li>• Diameter bottom [mm]: 260</li><li>• Height[mm]: 440</li><li>• Net weight [g]: approx. 1200</li></ul>	<b>Range of Application:</b> <ul style="list-style-type: none"><li>• Power line construction</li><li>• Railway line construction</li><li>• Industrial construction</li><li>• Free climbing work</li><li>• ... and many others more.</li></ul>
<b>Information for use:</b> <p>Maximum service life: 5 years from first use.</p> <p><b>Visual and functional check</b> before use. If you recognize damage of webbing, corpus or bottom, it has to be withdrawn from operation.</p> <p><b>Inspection</b> in accordance with legal national guidelines but <b>at least once a year</b>.</p> <p>Writing or marking with solvent-based pencil on lifting webbing is not allowed.</p>	
<b>Certificates/ Assessments:</b> <p>Lifting load test executed by the „Sächsisches Textilforschungsinstitut e.V.“(STFI)</p>	

HP-TEC GmbH	Kirchenlamitzerstraße 100, D-95213 Münchberg	www.hp-tec-produkte.de
-------------	---	------------------------